

DESCRIPTION

WET CLUTCH FRICTION PLATE

FIELD OF THE INVENTION

5 The present invention relates to a wet clutch friction plate and, in particular, to an improvement of one formed from a core plate and a friction material bonded to a side face of the core plate, a plurality of oil channels being formed in the friction material so as to provide communication between inner and outer peripheral edges of the friction material.

10 BACKGROUND ART

 Such a wet clutch friction plate is already known, as disclosed in, for example, Japanese Patent Application Laid-open No. 2001-221252.

 In such a wet clutch friction plate it is necessary, for example, to improve frictional properties in order to suppress the occurrence of abnormal noise or
15 vibration due to stick-slip by stabilizing frictional properties when connection of the clutch is in transition even under conditions in which there is a small amount of oil (first problem), and it is also necessary to reduce the phenomenon of drag due to oil viscosity resistance when the clutch is disengaged (second problem).

 However, conventionally, countermeasures are taken against the first problem
20 by reducing the oil discharge properties by narrowing the width of the oil channels on the surface of the friction material, whereas countermeasures are taken against the second problem by enhancing the oil discharge properties by widening the width of the oil channels on the surface of the friction material, which is the opposite of the above-mentioned countermeasures; as a consequence, it is difficult to solve the two
25 problems simultaneously and, in reality, solution of one of the first and second problems is sacrificed in accordance with the intended application or the specification of the wet clutch.

DISCLOSURE OF THE INVENTION

The present invention has been accomplished under the above-mentioned circumstances, and it is an object thereof to provide a wet clutch friction plate that enables the first and second problems to be solved at the same time.

5 In order to attain the above object, in accordance with a first aspect of the present invention, there is provided a wet clutch friction plate comprising a core plate and a friction material bonded to a side face of the core plate, a plurality of oil channels being formed in the friction material so as to provide communication between inner and outer peripheral edges of the friction material, characterized in
10 that a plurality of oil channels having a discharge angle that discharge oil from an inner peripheral side to an outer peripheral side of the friction plate when the friction plate rotates and a plurality of oil channels having an inflow angle that draw oil in from the outer peripheral side to the inner peripheral side of the friction plate are mixed at substantially equal intervals.

15 In accordance with this first aspect, since the plurality of oil channels for promoting the inflow of oil and the plurality of oil channels for promoting the discharge of oil are mixed on the friction plate at substantially equal intervals, it is possible to stabilize the frictional properties by obtaining an appropriate inflow of oil uniformly in the peripheral direction even in a half-clutch state under conditions in
20 which there is a small amount of oil and prevent the occurrence of abnormal sound or vibration due to stick-slip, and when the clutch is disengaged it is possible to suppress the phenomenon of drag due to oil viscosity resistance by obtaining appropriate oil discharge properties uniformly in the peripheral direction.

 Further, in accordance with a second aspect of the present invention, in
25 addition to the first aspect, the friction plate is divided into a plurality of regions arranged in the peripheral direction, a plurality of oil channels parallel to each other are formed in the friction material of each region, and one oil channel and another oil channel that are positioned at opposite end parts in the peripheral direction of each region are given the discharge angle and the inflow angle respectively.

In accordance with this second aspect, since the plurality of oil channels in each section are parallel to each other, it is possible to easily form the plurality of oil channels having an inflow angle and a discharge angle.

The above-mentioned object, other objects, characteristics, and advantages of the present invention will become apparent from an explanation of preferred embodiments that will be described in detail below by reference to the attached drawings.

BRIEF DESCRIPTION OF DRAWINGS

FIG. 1 is a vertical sectional view of a wet clutch equipped with a friction plate related to a first embodiment of the present invention, FIG. 2 is a side view of the friction plate of FIG. 1, FIG. 3 is a side view of a friction plate related to a second embodiment of the present invention, FIG. 4 is a side view of a friction plate related to a third embodiment of the present invention, FIG. 5A is a graph showing torque vibration properties of a wet clutch employing a conventional friction plate, FIG. 5B is a graph showing torque vibration properties of a wet clutch employing the friction plate of the present invention, and FIG. 6 is a graph for comparing drag torque between a wet clutch employing a conventional friction plate and a wet clutch employing the friction plate of the present invention.

BEST MODE FOR CARRYING OUT THE INVENTION

Preferred embodiments of the present invention are explained below by reference to the attached drawings.

A first embodiment of the present invention shown in FIG. 1 and FIG. 2 is now explained.

In FIG. 1, reference symbol C denotes an automobile automatic transmission wet clutch. A clutch housing 1 of this clutch C is formed by connecting a cylindrical portion 3 and a hub 4 to outer and inner peripheral ends respectively of an end wall 2, and the hub 4 is spline-coupled to an input shaft 5. An output shaft 6 integrally equipped with a drive gear 7 is relatively rotatably supported on the input shaft 5,

and a clutch inner 8 integrally connected to the output shaft 6 is concentrically disposed within the cylindrical portion 3.

A pressure piston 10 forming a hydraulic chamber 11 between itself and the end wall 2 is slidably fitted between an inner peripheral face of the cylindrical portion 3 and an outer peripheral face of the hub 4, and a return spring 12 urging the pressure piston 10 toward the hydraulic chamber 11 side is provided in a compressed state between the pressure piston 10 and the hub 4. A hydraulic oil supply/discharge hole 13 communicating with the hydraulic chamber 11 is provided in the hub 4.

A plurality of metal clutch plates 14 are slidably spline-fitted to the inner peripheral face of the cylindrical portion 3 so as to adjoin the outer side of the pressure piston 10, and a plurality of friction plates 15 of the present invention are slidably spline-fitted onto an outer peripheral face of the clutch inner 8, the clutch plates 14 and the friction plates 15 being alternately superimposed. Furthermore, a pressure-receiving plate 16 facing an outer face of the friction plate 15 on the outermost side is spline-fitted into the cylindrical portion 3, and this pressure-receiving plate 16 is prevented from moving axially outward by a retaining ring 17 latched on the cylindrical portion 3.

This clutch C is partially immersed in an oil reservoir in a base portion of a transmission case where oil accumulates, and the oil is supplied for cooling during rotation.

The friction plate 15 of the present invention is now explained by reference to FIG. 1 and FIG. 2.

The friction plate 15 is formed from a metal core plate 20 and a friction material 21 bonded to opposite sides of the core plate 20 by means of an adhesive, etc., and each friction material 21 is provided with a plurality of oil channels 22 extending in a straight line and providing communication between inner and outer peripheral edges of the friction material 21.

The friction plate 15 is divided into a plurality of regions A arranged in the peripheral direction, the friction material 21 of each region A is provided with a plurality of oil channels 22, which are parallel to each other, and an oil channel 22(c) at the center in the peripheral direction of each region A is positioned on a radial line L of the friction plate 15. Here, ends, on the inner peripheral side of the friction plate 15, of the oil channels 22 are called inner ends, and ends on the outer peripheral side are called outer ends.

In each region A, the oil channels 22 on the rear side along a rotational direction R of the friction plate 15 relative to the central oil channel 22(c) are given an inflow angle α such that the oil channel 22 is inclined forward in the rotational direction R of the friction plate 15 relative to a radial line L of the friction plate 15 passing through the inner end of the oil channel 22, whereas the oil channels 22 on the front side along the rotational direction R are given a discharge angle β such that the oil channel 22 is inclined rearward in the rotational direction R of the friction plate 15 relative to a radial line L of the friction plate 15 passing through the inner end of the oil channel 22. In the case of this first embodiment, the inflow angle α of the oil channel 22(a) in a rear end portion along the rotational direction R of each region A is equal to the discharge angle β of the oil channel 22(b) in a front end portion along the rotational direction R.

A triangular small piece 21a of the friction material 21 remains at the boundary between adjacent regions A and A of the friction material 21.

In the case of this embodiment, a large number of friction materials 21 cut into a strip shape are bonded to the core plate 15 at fixed intervals, and the oil channels 22 are formed therebetween.

The rotational direction R of the friction plate 15 referred to here means the direction of rotation of the friction plate 15 relative to the clutch plate 14.

The operation of this first embodiment is now explained.

When hydraulic pressure is supplied to the hydraulic chamber 11 of the clutch C, the pressure piston 10 receives the hydraulic pressure and moves forward against

the load of the return spring 12, that is, it slides toward a group of the friction plates 15 and the clutch plates 14 and clamps them between itself and the pressure-receiving plate 16, and the friction plates 15 and the clutch plates 14 are thus frictionally engaged with each other. The clutch C, which thereby attains a clutch ON state, allows a force to be transmitted from the input shaft 5 to the output shaft 6. Furthermore, when the hydraulic pressure is released from the hydraulic chamber 11, the pressure piston 10 retreats due to the load of the return spring 12, the friction plates 15 and the clutch plates 14 are freed, and the clutch C attains a clutch OFF state in which the transmission of force between the input shaft 5 and the output shaft 6 is cut off.

In such a clutch OFF state or in a half clutch state, relative rotation occurs between the friction plates 15 and the clutch plates 14 due to relative rotation between the input shaft 5 and the output shaft 6. In this process, when the friction plate 15 rotates relative to the clutch plate 14 in the direction shown by arrow R, in each region A of each friction material 21, the oil channels 22 given the inflow angle α exhibit a screw pump action as a result of cooperation with the adjacent clutch plate 14, thus drawing in the oil that is in contact with the outer periphery of the friction plate 15 toward the inner peripheral side of the friction material 21 through the oil channels 22 as shown by arrows N in FIG. 2, whereas the oil channels 22 given the discharge angle β exhibit a screw pump action as a result of cooperation with the adjacent clutch plate 14, thus pushing out the oil within the oil channels 22 toward the outer peripheral side of the friction material 21 as shown by arrows M in FIG. 2.

In this way, since the plurality of oil channels 22 for promoting the inflow of the oil and the plurality of oil channels 22 for promoting the discharge of the oil are mixed on the friction plate 15 at substantially equal intervals, it is possible to stabilize the frictional properties by obtaining an appropriate oil inflow uniformly in the peripheral direction even in a half-clutch state under conditions in which there is a small amount of oil and prevent the occurrence of abnormal sound or vibration due to stick-slip,

and when the clutch is disengaged it is possible to suppress the phenomenon of drag due to oil viscosity resistance by obtaining appropriate oil discharge properties uniformly in the peripheral direction.

In accordance with a test, it has been confirmed that as shown in FIG. 5A, in a clutch into which a conventional friction plate is incorporated, when the transmission torque of the clutch is increased under conditions in which there is a small amount of oil, severe vibration occurs, particularly where the torque is high, whereas as shown in FIG. 5B in the case of the present invention, the vibration is greatly suppressed throughout the region. Furthermore, as shown in FIG. 6, it has been confirmed that the drag torque in the clutch OFF state can be greatly reduced in the case of the present invention.

A second embodiment of the present invention shown in FIG. 3 is now explained.

In this second embodiment, in each of the regions A into which a friction plate 15 is divided in the peripheral direction, a plurality of parallel oil channels 22 are disposed so that an inflow angle α of an oil channel 22(a) in a rear end part along a rotational direction R of the region A is larger than a discharge angle β of an oil channel 22(b) in a front end part along the rotational direction R. Since the arrangement is otherwise the same as that of the preceding embodiment, parts in FIG. 3 corresponding to the preceding embodiment are denoted by the same reference numerals and symbols as those of the preceding embodiment, and duplication of the explanation is thus avoided.

The friction plate 15 of this second embodiment is particularly effective in a clutch for which the stability of frictional properties is important.

In this way, by appropriately differentiating the inflow angle α of the oil channel 22 in the rear end part and the discharge angle β of the oil channel 22 in the front end part along the rotational direction R in each of the regions A into which the friction plate 15 is divided, the frictional properties can be adjusted.

A third embodiment of the present invention shown in FIG. 4 corresponds to one obtained by removing triangular small pieces 21a of friction material present at the boundary between adjacent regions A and A of the friction plate 15 in the above-mentioned second embodiment.

5 The present invention is not limited to the above-mentioned embodiments, and may be modified in a variety of ways as long as the modifications do not depart from the spirit and scope thereof. For example, in the above-mentioned embodiments, the friction material 21 is bonded to the core plate 20 in the form of strip-shaped pieces so as to form the oil channels 22, but oil channels 22 may be
10 formed by bonding an annular sheet of friction material to a core plate 20 and then embossing or cutting the surface of the friction material 21. Furthermore, in the above-mentioned embodiments, the friction material 21 is bonded to opposite sides of the core plate 20 of the friction plate 15, which is spline-fitted onto the clutch inner 8, and the clutch plate 14, which is spline-fitted into the clutch housing 1 and which
15 does not have the friction material, is disposed between the friction plates 15, but friction plates 15 may be spline-fitted to each of a clutch inner 8 and a clutch housing 1, and a friction material 21 may be bonded to only one side of core plates 20 thereof that face each other.